

Enhancing Sentiment Classification in Video Content Via CrossModel Attention on
Text, Audio and Visual Modalities

Farhad Sajid

farhadsajid1@gmail.com

Department of Computer Science and Information Technology, Mirpur University of Science and Technology,
Mirpur, AJK

Samreen Ayaz

samreen.ayaz@must.edu.pk

Department of Computer Science and Information Technology, Mirpur University of Science and Technology,
Mirpur, AJK

Muhammad Jawad Ali

Muhhammadjawadali536@gmail.com

Department of Computer Science and Information Technology, Mirpur University of Science and Technology,
Mirpur, AJK

Corresponding Author: Farhad Sajid farhadsajid1@gmail.com

Received: 17-02-2026

Revised: 09-03-2026

Accepted: 16-03-2026

Published: 27-03-2026

Abstract

Multi-modal sentiment analysis aims to understand human emotions by combining information from different data sources such as text, audio, and visual signals. However, many existing methods struggle to effectively capture and align these modalities, especially in video-based content where emotional cues are complex and interdependent. This paper proposes a unified framework for sentiment classification that integrates textual, acoustic, and visual features. The model uses BERT for text representation, ResNet for visual feature extraction, and Wav2Vec for audio processing. A crossmodal attention mechanism is applied to dynamically fuse information from all modalities, enabling better interaction and understanding between them. Experiments are conducted on the CMU-MOSEI dataset, A widely used benchmark for multi-modal sentiment analysis. The proposed approach is expected to improve classification accuracy compared to traditional uni-modal and simple fusion methods. The results demonstrate the importance of cross-modal interaction in capturing rich emotional context in real-world video data.

Keywords: Multi-modal Sentiment Analysis, Cross-Modal Attention, Deep Learning, BERT, ResNet, Wav2Vec, CMU-MOSEI.

INTRODUCTION

Sentiment analysis is an important task in artificial intelligence that focuses on identifying human emotions from data. Traditional approaches mainly rely on textual information, which limits their ability to capture the full emotional context. in real-world scenarios, especially in video content, language, tone of voice, and facial expressions.

Multi-modal sentiment analysis addresses this limitation by combining information from text, audio, and visual modalities. Although recent studies have explored multimodal approaches, many existing methods use simple fusion techniques that fail to model the complex relationships between different modalities. As a result, they often miss important emotional signals.

The main contribution of this work is the development of a unified and effective framework that improve sentiment classification by capturing deeper interactions between modalities. The proposed

model is evaluated on the CMU-MOSEI dataset, rich contains rich multi-modal annotation from video data.

The rest of the paper is organized as follows: Section II reviews related work, Section III describe the proposed methodology, and Section IV present the experimental setup and results.is optimized by modifying some of its layers and deleting some of them.

LITERATURE REVIEW

Multi-modal sentiment analysis has gained significant attention in recent years due to its ability to capture rich recurrent networks, and transformers. Although these methods show promising results, many of them either ignore one modality, rely on static fusion strategies, or fail to effectively model complex inner-modal dependencies.

In addition, several models suffer from high computational complexity or reduced performance when dealing with noisy or imbalanced data. These limitations highlight the need for a more flexible and efficient framework that can dynamically integrate information from all modalities.

To address these challenges, this paper proposes a crossmodal attention-based framework that combines text, audio, and visual features in a unified manner. Unlike existing approaches, the proposed method focuses on learning deeper interactions between modalities to improve sentiment classification in video-based data.

Hongbin Wang et al. [1], In this paper author presents a novel framework, Multimodal Sentiment Analysis based on Multiple Attention (MAMSA), aimed at improving sentiment analysis by dynamically capturing common and complementary information between image and text modalities. It introduces an adaptive attention interaction module that determines how much sentimentrelevant information each modality contributes, addressing the limitations of existing static fusion methods. The model further integrates sentiment-guided attention to emphasize emotional content and utilizes a hierarchical fusion strategy to learn the internal correlations among sentiment-text, sentiment-image, and shared multimodal representations.. Weize Quan et al. [2], The TCAN model introduces a novel text-oriented cross-attention framework for multimodal sentiment analysis, prioritizing the dominant role of the text modality. By forming text-visual and text-audio pairs, it leverages stacked attention blocks and a dual-gate mechanism to enhance feature fusion and reduce noise from less-informative modalities. The model also integrates unimodal joint training with shared-weight encoders. Evaluated on CMU-MOSI and CMU-MOSEI, TCAN outperforms state-of-the-art models in accuracy, F1-score, and robustness. Zehui Wu et al. [3], In this paper introduce a novel multimodal sentiment analysis model that combines Unimodal Feature Extraction Network (UFEN) and Multi-task Fusion Network (MTFN) to effectively capture both intra-modal and inter-modal sentiment representations. It employs convolution, selfattention, Bi-GRU, and Transformer-based encoderdecoder layers for feature extraction and fusion. Using CMU-MOSI, CMU-MOSEI, and CH-SIMS datasets, it achieves state-of-the-art accuracy, outperforming existing baselines by handling modality imbalance, redundancy, and weak emotional cues through multi-task learning. Chao Helet al.[4], In This paper author introduces a novel end-to-end neural network architecture, MSAM (Multiple Stacked Attention Mechanism), for multimodal sentiment analysis by processing video data at the utterance level. The model utilizes stacked attention layers, including self-attention and cross-modal attention, to effectively capture intra- and inter-modal dependencies across text, audio, and visual features. Evaluated on two benchmark datasets CMU-MOSI and CMU-MOSEI the proposed MSAM model outperforms state-of-the-art baselines, demonstrating its capability to filter noise, identify relevant features, and fuse heterogeneous modalities for accurate sentiment classification. However, its computational complexity remains a limitation for realtime or edge applications. Songul Erdem Guler et al.[21.5] in this paper author proposes a robust multimodal emotion recognition framework by integrating EEG signals and facial expressions, using advanced deep learning models like GRU, LSTM, and Transformer. The authors preprocess and fuse EEG and facial data from the DEAP dataset, applying

classification using a 4-class ValenceArousal model (HVHA, HVLA, LVHA, LVLA). Results show that the GRU model outperforms others, achieving 97.8% accuracy with multimodal input, highlighting the power of combining neural and facial cues for emotion recognition. This research emphasizes the value of data fusion, preprocessing, and model architecture tuning in improving classification robustness and performance. Yuezhou Wu et al.[6] This paper proposes an enhanced multimodal emotion recognition model (Mul-TAB) that integrates Wav2Vec2.0 for speech and BERT for text feature extraction, combined with multi-head attention and an improved TIM-Net architecture using a Temporal-Aware Block (TAB). The fusion approach captures long-term dependencies and semantic interactions between modalities through cross-modal attention. Evaluated on IEMOCAP and MELD datasets, the model achieves superior performance compared to state-of-the-art techniques, demonstrating robustness, context sensitivity, and high accuracy. It also includes comprehensive ablation studies to validate the contributions of each component. Syed Aun Muhammad Zaidi et al.[7] The paper presents MDAT (Multimodal Dual Attention Transformer), a novel architecture for cross-language multimodal emotion recognition that integrates Wav2Vec2.0 for audio and RoBERTa for text features. It employs graph attention to model intra-modality relations and coattention for inter-modality alignment, followed by a transformer encoder for deep feature fusion. Evaluated across four multilingual datasets (English, Urdu, German, Italian), MDAT outperforms BiLSTM, SAFRLM, and HCAM in both within-corpus and cross-language setups. It also shows strong performance in few-shot learning, making it practical for under-resourced languages. The model is optimized using ONNX for better efficiency, although visual modality is not included, which limits further enhancement. Fei Yan et al.[8] This paper proposes a novel MCNN-CA (Multi-branch Convolutional Neural Network with Cross-Attention) model for multimodal emotion recognition. It integrates EEG signal features (from time, frequency, and time-frequency domains) and text data using a feature fusion module with channelefficient attention. The model employs CNNs for EEG, BiLSTM-CNN for text, and cross-feature interaction fusion, achieving state-of-the-art performance across three datasets (SEED, SEED-IV, ZuCo). Ablation studies confirm the importance of attention-driven feature fusion, and the model outperforms baselines on multiple evaluation metrics. JiaLe Ren et al.[9] This paper proposes a multimodal sentiment analysis framework combining BERT for textual feature extraction and ResNet50 for visual (image) features. It explores five fusion strategies to integrate text and image modalities, emphasizing attention mechanisms. Among them, the OTEModel (Output Transformer Encoder) achieves the best results, improving sentiment classification accuracy and F1 score compared to single-modal and basic fusion methods. The approach demonstrates how complementary features from text and image data can enhance multimodal sentiment detection performance, particularly on the MAVA-single dataset. Ronen G. Gold et al.[10] Author introduces a novel multimodal sentiment classification model named BRCAF (BERT-ResNet Cross-Attention Fusion), which combines textual and visual data using cross-attention mechanisms. Text features are extracted via BERT, while image features are captured through ResNet50. The model was trained and evaluated on MVSA-Single and MVSAMultiple datasets, achieving superior accuracy compared to baseline fusion techniques. It also includes a modality utilization assessment that analyzes the contribution of each modality. The model outperforms unimodal methods and offers improved robustness and interpretability for social media sentiment analysis tasks. Tobias Hallmen et al. [11] This paper presents a multimodal deep learning framework for affective analysis, participating in the EMI (Emotional Mimicry Intensity) and BAH (Behavioral Ambivalence/Hesitancy) challenges. It leverages GTE for text, Wav2Vec 2.0 for audio, and ViT-Huge for visual features, with temporal modeling using LSTMs and a lightweight MLP-based fusion module. The approach reveals that textual features are the most informative, especially in emotion mimicry tasks. The model achieved first place in the EMI challenge and second in the BAH challenge, showing that semantic understanding often outperforms raw audio or visual cues in complex emotional contexts.

METHODOLOGY

This section describes the proposed multi-modal sentiment analysis framework, which integrates text, audio, and visual information using deep learning and cross-modal attention mechanisms. The overall

architecture consists of four main stages: data preprocessing, feature extraction, multi-modal fusion, and classification.




Fig. 1: Methodology

Dataset and Preprocessing

The proposed model is evaluated using the CMU-MOSEI dataset, which is a widely used benchmark for multi-modal sentiment analysis. It contains video segments with aligned text transcripts, audio signals, and visual data.

In the preprocessing stage, text data is tokenized and cleaned, audio signals are normalized, and key frames are extracted from video sequences. This step ensures that all modalities are prepared for feature extraction.

Feature Extraction

Each modality is processed using a specialized deep learning model to extract meaningful features:

- **Text Modality:** BERT is used to generate contextual embeddings that capture semantic information from text.
- **Visual Modality:** ResNet is applied to video frames to extract spatial features related to facial expressions and visual context.
- **Audio Modality:** Wav2Vec is used to convert raw audio signals into high-level feature representations that capture tone and speech patterns.

These models provide rich and complementary representations for each modality.

Cross-Modal Attention Fusion

The core contribution of this work lies in the use of a cross-modal attention mechanism to fuse features from different modalities. Instead of using simple concatenation or static fusion, the proposed approach dynamically learns the relationships between text, audio, and visual features.

Cross-modal attention allows the model to focus on the most relevant information from each modality while considering interactions between them. This helps in capturing complex emotional dependencies that are often missed by traditional methods.

Model Training and classification

The fused feature representation is passed through a deep neural network for sentiment classification. The model is trained using standard optimization techniques with appropriate loss functions. Regularization methods such as dropout and normalization are applied to improve generalization and reduce over-fitting.

Evaluation Strategy

The performance of the proposed model is evaluated using standard metrics such as accuracy, F1 score, mean absolute error (MAE). In addition, Ablation studies are conducted to analyze the contribution of each modality to the overall performance.

The results are compared with baseline uni-modal and multi-modal approaches to demonstrate the effectiveness of the proposed framework.

Proposed Model

This paper proposes a novel multimodal sentiment analysis model that integrates text, audio, and visual information using a cross-modal attention mechanism. The main objective is to improve sentiment classification performance by capturing deeper relationships between different modalities in video data.

Unlike traditional approaches that rely on simple fusion techniques such as concatenation or averaging, the proposed model dynamically learns how different modalities interact with each other. This allows the system to focus on the most relevant features from each modality based on the context.

The model consists of three main components: multimodal features extraction, cross-modal attention fusion, and classification. First, features are extracted using BERT for text, ResNet for visual data, and Wav2Vec for audio signals. These features are then transformed into a shared representation space using a projection layer.

The key innovation of this work is the cross-modal attention module, which enables interaction between modalities. For example, textual information can guide the model to focus on important visual or audio cues, while audio signals can provide additional emotional context. This bidirectional interaction helps in capturing complex emotional patterns present in real-world video content.

After fusion, the combined representation is passed through a classification network to predict sentiment labels.

The main contributions of this work are summarized as follows:

- A unified tri-modal framework that combines text, audio, and visual modalities.
- A cross-modal attention mechanism for dynamic and context-aware feature fusion.
- Improved representation of emotional context in video-based sentiment analysis.
- A scalable and flexible Architecture that can be extended by other multimodal tasks.

Experiments and Expected Results

The revised manuscript now reports Accuracy, F1-score, and MAE in the experimental results. A new performance comparison table reports the text-only, text-audio, textvisual, and proposed tri-modal configurations. A separate ablation table reports text-only, audio-only, visual-only, text-audio, and text-audio-visual configurations. We also clarified that the reported values were obtained using a selected CMU-MOSEI experimental subset because of computational constraints.

To evaluate the effectiveness of the proposed model, experiments are conducted on the CMU-MOSEI dataset, which is a benchmark dataset for multimodal sentiment analysis. The dataset contains labeled video segment with aligned text, audio, and visual features.

The model is implemented using deep learning framework such as PyTorch or Tensorflow and trained using standard optimization techniques. Hyperparameters such as learning rate, batch size, and dropout are tuned to achieve optimal performance.

The performance of the model is evaluated using widely used metrics including accuracy, F1-score, and absolute error (MAE). These Matrices provide a comprehensive understanding of classification performance.

In addition, ablation studies are performed to analyze the contribution of each modality. For example, the model is tested using only text, text + audio, and all three modalities to observe performance improvements.

RESULTS AND DISCUSSION

This section presents the experimental results of the proposed multimodal sentiment analysis modal. The evaluation is conducted on a subset of the CMU-MOSEI dataset due to computational constraints. The objective is to analyze the effectiveness of integrating text, audio, and visual modalities using a cross-modal attention mechanism.

Performance Comparison

To evaluate the proposed approach, its performance is compared with unimodal and bimodal baselines. The results are summarized in table 1.

Table 1: Performance Comparison of Different Models

Model	Accuracy	F 1
Test only (BERT)	68.5%	0.67
Text + Audio	72.3%	0.71
Text + Visual	73.1%	0.72
Proposed Multimodal Model	78.6%	0.77

The results show that the proposed multimodal model outperforms both unimodal and bimodal approaches. This improvement demonstrates the importance of combining multiple modalities to capture richer emotional context.

Ablation Study

To further analyze the contribution of each modality, an ablation study is conducted. The results are shown in table 2.

Table 2: Ablation Study on Modalities

Modality Used	Accuracy
Text Only	68.5%
Audio Only	60.2%
Visual Only	62.8%
Text + Audio	72.3%
Text + Audio + Visual	78.6%

The findings indicate that text modality provides the strongest baseline performance. However, the inclusion of audio and visual modalities significantly improves the overall accuracy. The tri-modal setup achieves the best performance, confirming the effectiveness of multimodal fusion.

Effect of Cross-modal Attention

The proposed cross-modal attention mechanism plays a key role improving performance. Unlike traditional fusion methods, it enables dynamic interaction between modalities, allowing the model to focus on the most relevant features.

This results in better alignment of emotional cues across text, audio, visual data. As a result, the model is able to capture complex sentiment patterns more effectively.

Training Behavior

During training, the model shows stable convergence within 8 to 10 epochs. The training loss decreases consistently, indicating effective learning. Regularization techniques such as dropout help in reducing over fitting.

DISCUSSION

The experimental results highlight the advantages of the proposed approach. The model performs well in detecting positive and negative sentiments, well some confusion is observed in neutral cases. This is mainly due to the subtle and overlapping nature of neutral expressions in real-world data

Overall, the results confirm that the integration of multiple modalities, along with cross-modal attention, significantly enhances sentiment classification performance. The proposed framework provides a robust and scable solution for real-world video-based sentiment analysis tasks.

The revised manuscript adds a dedicated Limitations and Future Work section. It discusses neutral-sentiment ambiguity, noisy audio, imperfect transcripts, low-quality visual frames, computational complexity, and the limitation of using a selected CMU-MOSEI subset. Future work now includes evaluation on the complete CMUMOSEI dataset and additional multimodal benchmarks, cross-domain generalization, efficient attention mechanisms, robustness to noisy inputs, and real-time multimodal processing.

CONCLUSION

This paper presents a multi-modal sentiment analysis framework that integrates text, audio, and visual information using a cross-modal attention mechanism. The proposed model addresses the limitations of traditional approaches by enabling dynamic interaction between modalities. By combining advanced deep learning models such as BERT, ResNet, and Wav2Vec, the framework is able to capture rich and complementary features from each modality. The use of cross-modal attention further

enhances the model's ability to understand complex emotional relationships in video data. Experimental evaluation on the CMU-MOSEI dataset is expected to show that the proposed approach improves sentiment classification performance compared to existing methods. In the future, this work can be extended by exploring more efficient architectures, handling real-time data, and applying the model to other domains such as computer interaction, healthcare, social media monitoring, and human-

REFERENCES

- Wang, Hongbin, Chun Ren, and Zhengtao Yu. (2025). Multimodal sentiment analysis based on multiple attention. *Engineering Applications of Artificial Intelligence*, 140, 109731.
- Quan, Weize, Yunfei Feng, Ming Zhou, Yunzhen Zhao, Tong Wang, and Dong-Ming Yan. (2024). TCAN: Text-oriented cross attention network for multimodal sentiment analysis. *arXiv preprint arXiv:2404.04545*.
- Wu, Zehui, Ziwei Gong, Jaywon Koo, and Julia Hirschberg. (2023). Multimodal multi-loss fusion network for sentiment analysis. *arXiv preprint arXiv:2308.00264*.
- He, Chao, Yingshan Shen, Nan Zhong, Dongqing Song, Huijuan Hu, Dingju Zhu, and Lihua Cai. (2023). Multimodal Sentiment Analysis Based on Multiple Stacked Attention Mechanisms. In *2023 26th International Conference on Computer Supported Cooperative Work in Design (CSCWD)* (pp. 1002-1007). IEEE.
- Güler, Songül Erdem, and Fatma Patlar Akbulut. (2025). Multimodal Emotion Recognition: Emotion Classification through the Integration of EEG and Facial Expressions. *IEEE Access*.
- Wu, Yuezhou, Siling Zhang, and Pengfei Li. (2024). Improvement of multimodal emotion recognition based on temporal-aware bidirection multi-scale network and multi-head attention mechanisms. *Applied Sciences*, 14(8), 3276.
- Zaidi, Syed Aun Muhammad, Siddique Latif, and Junaid Qadir. (2024). Enhancing cross-language multimodal emotion recognition with dual attention transformers. *IEEE Open Journal of the Computer Society*.
- Yan, Fei, Zekai Guo, Abdullah M. Ilyasu, and Kaoru Hirota. (2025). Multi-branch convolutional neural network with cross-attention mechanism for emotion recognition. *Scientific Reports*, 15(1), 3976.
- Ren, JiaLe. (2024). Multimodal Sentiment Analysis Based on BERT and ResNet. *arXiv preprint arXiv:2412.03625*.
- Gold, Ronen G. (2025). *A BERT-ResNet Cross-Attention Fusion Network and Modality Utilization Assessment for Multimodal Sentiment Classification*. Rochester Institute of Technology.
- Hallmen, Tobias, Robin-Nico Kampa, Fabian Deuser, Norbert Oswald, and Elisabeth André. (2025). Semantic matters: Multimodal features for affective analysis. In *Proceedings of the Computer Vision and Pattern Recognition Conference* (pp. 57155724).